

UNIVERSAL BEVELLING MACHINES FOR EDGES UP TO 15MM

ITEM: KFH 17-15 R

Universal beveling machines equipped with booster technology that allows to increase the milling performance from 30% to 80% and to drastically reduce vibration compared to a traditional machine. Spring cushioning system for ideal preparation of the weld seam. Ergonomic FeinErgoGrip handle with two-hand control for fatigue-free work. Soft start, restart interlock, anti-lock control, electronic overload protection. Quick change of cutter to minimize machining interruptions. High stock removal capacity.

Tech. Code		N422200
Rated power connection	watt	1700
Rendered power	watt	1000
No-load speed	Rpm	2300-7500
Max length bevel to 45°	mm	15
Max height bevel to 45°	mm	10,6
Bevel angle		30°/37,5°/45°/60°
Radius	mm	3
Support plate	Ø	137
Cable with plug	m	4
Weight	Kg	6,4
Vibration exposure limit value	m/s²	ah, 3,7

Included:
Tool without cutter head, without guide roller, without inserts
Allen key 5 mm
6 clamping screws
Torx screwdriver TX15
Copper paste
Plastic tool case

Tech. Code		Accessories
N422201		Milling head for bevel 45° and rounded bevels
N422202		Guide roller ø 26.30 mm for 45 ° bevel
N422203		Guide roller ø 28.55 mm for 45 ° bevel
N422204		Straight plate kx cut for bevels
N422205		Straight plate kx cut for bevels
N422206		Cutting plate kX for r3 alu and soft materials
N422207		Cutting plate Kx for r3 universal applications
N422208		Clamping screws for cutting plate Kx

ANGLE GRINDERS

ITEM: WSG 17-125 PS

Compact angle grinders with optimal speed for using flap discs and fibre discs. POWERtronic device for high power and constant speed even under load. Blockage monitoring, accidental restart protection, soft start and electronic overload protection. Metal head for maximum strength and Industrial cable H07. Spindle lock button.

Tech. Code		N4223125
Power supply	V	230 - 50 Hz
Rated input power	W	1700
No-load speed	Rpm	8500
Flap disc Ø	mm	125
Backing pad Ø	mm	125
Mounting threaded spindle		M14
Weight	Kg	2.4

Included:
Wheel guard
Pair of flanges
Handle
Key

ITEM: WSG 20-230

High-power angle grinders for cutting and grinding.
High performance FEIN® motor with outstanding removal over the full working range up to 150 % load.
Flat drive head allows the tool to be plunged into workpieces. Soft start for safe handling, rear handle can be rotated through 4 positions.
Dustproof ball bearings, sealed electronic components. Spindle lock button.

Tech. Code		N4228230
Power supply	V	230-50 Hz
Rated input power	W	2000
No-load speed		6600
Grinding disc Ø	mm	230
Backing pad Ø	mm	230
Mounting threaded spindle		M14
Weight	kg	5.6

Included:
Wheel guard
Pair of flanges
Handle
Key