

2 HANDLING 3 ROUND COLUMN MOUNTED JIB CRANE WITH GIS SYSTEM KB PROFILE ARM

ITEM: M1250

Column mounted jib crane, model TER, with GIS system KB profile arm.

Features:

- Cold rolled profile, not bent, seamless
- Wear resistant cap spring brakes
- Finish: one coat of anti-rust paint and two coats of water-soluble varnish not suitable for outdoors or particularly damp environments

Advantages:

- Maximum smoothness guaranteed by the quality of the profile
- Maximum rigidity guaranteed by the geometry of the column
- Arm rotation up to 270°

Supplied with:

- Hoist trolley
- Power supply system with festoon flat cable system and cable trolleys
- Radius adjustable slew limiter
- Use and maintenance manual

ON-LINE MANUAL

Tech. Code		CAPACITY kg	MODEL	ARM LENGTH C mm	OUTERMOST POSITION OF HOOK B mm	A mm	F mm	G mm	Q mm	S mm	D mm	HOOK HEIGHT FROM GROUND Y mm	FOUNDATION TYPE**	EXTENSION TYPE	ANCHORING TIE ROD TRACTION kg	WEIGHT kg		
M125002003000		200	SC200/3000 TER	3000	2855	300	3385	4000	560	560	330	2900	6	1A	1440	310		
M125002004000			SC200/4000 TER	4000	3855		3382						7		1920	330		
M125002005000			SC200/5000 TER	5000	4855		3385						8		2400	345		
M125002503000		250	SC250/3000 TER	3000	2855	200	3382						8		1440	310		
M125002504000			SC250/4000 TER	4000	3855												1920	330
M125002505000			SC250/5000 TER	5000	4855												3385	2400
M125005004000		500	SC500/4000 TER	4000	3720	350	3140		740	620	400	2650	12	2	2130	465		
M125005005000			SC500/5000 TER	5000	4720								13		2660	490		
M125010004000		1000	SC1000/4000 TER	4000	3720								17		3960	580		
M125010005000			SC1000/5000 TER	5000	4720												18	4950

** For foundation and relative cages dimensions, look at page M. 27

Related products

GLOVES IN CONTINUOUS NYLON WIRE POLYURETHANE COATED

Tech. Code	Size	EU size
K23117	M	7
K23118	L	8
K23119	XL	9

The products are available in chapter K