



ITEM: A6045

Material Solid carbide
Standard Factory standard
Tolerance 0/+0.004
Flutes Spiral 7° - 8° variable pitch, - cutting right-hand

Surface finish Durable
Application High performance reaming on materials such as carbon steels, cast irons and stainless steels with $R \leq 1400 \text{ N/mm}^2$



< 500	< 850	< 1200	< 600	< 850	Duplex	< 240	< 300	< 10% Si	> 10% Si	Brass Copper	Ti6Al4V	HTA	< 45	< 60	< 65
●	●	●	●	●	●	○	○						●		

REAMER FACTORY STANDARD

Tech. Code		D mm	L mm	l1 mm	l mm	d mm	Z
A604503,98		3.98	75	39	12	6	4
A604503,99		3.99					
A604504		4.00					
A604504,01		4.01					
A604504,02		4.02					
A604504,5		4.50					
A604504,98		4.98					
A604504,99		4.99					
A604505		5.00					
A604505,01		5.01					
A604505,02		5.02					
A604505,5		5.50					
A604505,98		5.98					
A604505,99		5.99					
A604506		6.00					
A604506,01		6.01					
A604506,02		6.02					
A604506,5		6.50	100	64	16	8	6
A604507		7.00					
A604507,5		7.50					
A604507,98		7.98					

Tech. Code		D mm	L mm	l1 mm	l mm	d mm	Z		
A604507,99		7.99	100	64	16	8	6		
A604508		8.00							
A604508,01		8.01							
A604508,02		8.02							
A604508,5		8.50							
A604509		9.00							
A604509,5		9.50	120	60	20	10			
A604509,98		9.98							
A604509,99		9.99							
A604510		10.00							
A604510,01		10.01							
A604510,02		10.02							
A604510,5		10.50							
A604511		11.00							
A604511,5		11.50							
A604511,98		11.98							
A604511,99		11.99							
A604512		12.00		75		12			
A604512,01		12.01							
A604512,02		12.02							

Related products

PNEUMATIC COUNTERSINKS

Tech. Code	Collet mm	Power Watt	Rpm max.
L119025	10 - ER16	100	500

The products are available in chapter L