ELEMATIC INSULATING ADHESIVE TAPES

ITEM: N9422

Insulating adhesive tapes in PVC self-extinguishing with a high degree of electrical isolation (600 V) and mechanical protection for any applications in civil and industrial plants.

Features:

- Stretching at breaking point: 200% - Electric rigidity: 40 kV/mm - Operating temperture: -18 / +90°C

| Tech. Code | | N942215N | N942219N | N942219B | N942219R | N942225N | N942225B |
|------------|----|----------|-----------|----------|----------|----------|----------|
| | | | | | | | |
| Colour | | Bla | ick | White | Red | Black | White |
| Width | mm | 15 | 19 25 | | 5 | | |
| Thickness | mm | | 0,13 0,15 | | | | |
| Length | m | 10 | 25 | | | | |
| | * | | | | | | |

Conformity with the standard regulations CEI EN 60454-3-1 e BS 3924 VDE nr. 40039640

ADHESIVE FABRIC-REINFORCED TAPES

ITEM: N9430

Reinforced, high adherence, waterproof, suitable for packing, repairing, joining and protecting a wide range of materials. Silver.

| Tech. Code | N943050/25 |
|------------|------------|
| | |
| Height mm | 50 |
| Length m | 25 |

ADHESIVE FABRIC-REINFORCED TAPES

ITEM: 5080

Triple-layer highly tear resistant and waterproof up to four atmospheres, temperature resistant from -10°C to +70°C, suitable for high-sealing emergency repair. Silver.

| Tech. Code | N944050/50 |
|------------|------------|
| | |
| Height mm | 50 |
| Length m | 50 |

TAPE STRETCHERS

ITEM: N9450

Plastic body, adjustable clutch, suitable for tapes with a height of up to 50 mm.

| reading proof, and assessed states of the first states of the states of | | | | |
|---|----------|--|--|--|
| Tech. Code | N9450S50 | | | |
| | | | | |