

MOUNTED POINTS WITH PINK ALUMINUM OXIDE

ITEM: ZY

Made with pink aluminum oxide and vitrified bond. For universal use on all kind of steel and cast iron. Made in Italy with high quality raw material in order to give a consistent cut rate and a good surface finish.

Specification of the mixture: AR - Abrasive (Pink corundum), P - Hardness (High), 5 - Structure (Close), V - Bond (Vitrified ceramic).

Cylindrical shape

Tech. Code		G540630206100	G540630306080	G540630408080	G540630510080	G540630612080	G540630812080
D x T	mm	2 x 6	3 x 6	4 x 8	5 x 10	6 x 12	8 x 12
Shank	mm	3 x 38					
Specification		AR 100 P5V	AR 80 P5V				
							

Tech. Code		G540631012060	G540660610060	G540660612100	G540660810080	G540661015060
D x T	mm	10 x 12	6 x 10	6 x 12	8 x 10	10 x 15
Shank	mm	3 x 38	6 x 40			
Specification		AR 80 P5V	AR 60 P5V	AR 100 P5V	AR 80 P5V	AR 60 P5V

Tech. Code		G540661215060	G540661520046	G540662020046	G540662525046	G540663232036
D x T	mm	12 x 15	15 x 20	20 x 20	25 x 25	32 x 32
Shank	mm	6 x 40				
Specification		AR 60 P5V	AR 46 P5V			AR 36 P5V
						

ITEM: KU

Spherical shape

Tech. Code		G5411306080	G5411308080	G5411310060
D	mm	6	8	10
Shank	mm	3 x 38		
Specification		AR 80 P5V		AR 60 P5V

Tech. Code		G5411610060	G5411612060	G5411615046	G5411620046
D	mm	10	12	15	20
Shank	mm	6 x 40			
Specification		AR 60 P5V		AR 46 P5V	
					

ITEM: SP

Ogival shape

Tech. Code		G541661220060	G541662032046
D x T	mm	12 x 20	20 x 32
Shank	mm	6 x 40	
Specification		AR 60 P5V	AR 46 P5V

ITEM: KE

Conical shape

Tech. Code		G542161025060	G542162032046
D x T	mm	10 x 25	20 x 32
Shank	mm	6 x 40	
Specification		AR 60 P5V	AR 46 P5V

