

SHANK MOUNTED FELT BOBS

The felt rotary tools are produced with 100% best-quality Australian wool. Suitable for use with diamond paste to produce a mirror finish on moulds for plastics, dies etc.
Shank Ø 3x30 mm. Recommended speed 5-10m/sec. Length tolerance ±5%.

Tech. Code		G58559X153MO	G585013X203MO	G584510X303MO	G584020X303MO
Dimensions	mm	9 x 15	12 x 20	10 x 30	20 x 30
Shank Ø	mm	3			
Material		Soft white felt			

SHANK MOUNTED SOFT FELT WHEELS

Shank mounted soft felt wheels.

Tech. Code		G5875D212,35	G5875D252,35
Dimensions Ø	mm	21	25
Shank Ø	mm	2.35	
Material		Soft felt	

ROTARY FELT LAPPING TOOLS WITH SYNTHETIC SUPPORT

Flexible body, steel shank.

Tech. Code		G5880D123	G5880D203	G5880D332	G5880D486
Description		Felt pad			
Dimensions Ø	mm	12	20	32	48
Shank Ø	mm	3			6

SELF-ADHESIVE FELT DISCS

Replacement for rotary supports.

Tech. Code		G588512X3	G588520X3	G588532X3	G588548X3
Description		Felt pad			
Dimensions Ø	mm	12	20	32	48

SHANK MOUNTED SOFT COTTON STRING BUFFS

Cotton wheel buffs of various sizes 21 mm, 30 mm and 40 mm, all with Ø 2.35 mm shank.

Tech. Code		G5935D21G2,35M	G5935D21G2,35D	G5935D30G2,35D	G5935D40G2,35D
Dimensions	mm	21		30	40
Shank Ø	mm	2.35			
Material		Soft cotton	Double twisted cotton		
					