

SAF-FRO OXYGEN PRESSURE REDUCERS

ITEM: EUROFRO

EN ISO 2503. Full-protection covered gauges, ABS shockproof, detachable hose connection for Ø 8 mm pipe with G 3/8 DX nut.

Tech. Code		Entry scale bar	Exit scale bar	Max. press. bar
J77110		0 – 300/315	0 – 15/16	10

SAF-FRO ACETYLENE PRESSURE REDUCERS

ITEM: EUROFRO

EN ISO 2503. Full-protection covered gauges, ABS shockproof, detachable hose connection for Ø 8 mm pipe with G 3/8 DX nut.

Tech. Code		Entry scale bar	Exit scale bar	Max. press. bar
J771401		0 – 40	0 - 2.5	1,5

SAF-FRO PROPANE PRESSURE REDUCERS

ITEM: EUROFRO

EN ISO 2503. Full-protection covered gauges, ABS shockproof, detachable hose connection for Ø 8 mm pipe with G 3/8 DX nut.

Tech. Code		Scale bar	Max. press. bar
J771501		0 – 6	4

SAF-FRO ARGON PRESSURE REDUCERS WITH FLOW METER

ITEM: EUROFRO

EN 13918, double regulation for greater flow stability, with the option of closing the gas without changing the settings. Protection cover, rubber gauge, detachable hose connection for Ø 6 mm pipe with G 1/4 SX nut.

Tech. Code		Manometer scale bar	Flowmeter scale L/min
J771901		0 – 300/315	0 - 20