

SAF-FRO QUALITY CONTROL OF WELDED JOINTS

ITEM: 1 - FLUXO S190 SOLVENTE

[SAFETY DATA SHEETS ON-LINE](#)

Cleaner for removing oil, dirt, paint, rust, moisture, and miscellaneous residues.

An optimal preventive cleaning in order to allow the penetrating agent to seep in without obstacles, even in the most microscopic crack, is essential for detecting defects.

Tech. Code		Package	Quantity ml	
J8411400		Spray can	500	12

ITEM: 2 - FLUXO P125 PENETRANTE

[SAFETY DATA SHEETS ON-LINE](#)

Penetrating product for application on surfaces to be inspected. Applied on wet surfaces, it seeps into gaps by capillary action.

Tech. Code		Package	Quantity ml	
J8412400		Spray can	500	12

ITEM: 3 - FLUXO R175 RIVELANTE

[SAFETY DATA SHEETS ON-LINE](#)

The developer absorbs and draws the penetrating agent left over in the gap to the surface, allowing the red colorations to be seen in contrast with the white background.

Tech. Code		Package	Quantity ml	
J8414400		Spray can	500	12

PROTECTIVE CERAMIC FOR WELDING

ITEM: SF 7900

[SAFETY DATA SHEETS ON-LINE](#)

Ceramic protector without silicon, long-lasting (up to 8 hours before re-application), dry to the touch in seconds. Prevents adhesion of molten metal splashes on threaded guides, torch nozzles and parts to be welded. Very effective on laser and plasma nozzles, eliminates cleaning downtime in automated welding systems with considerable time-savings.

Tech. Code		Package	Quantity ml	
J8420400		Spray can	400	12

SAF-FRO ANTI-ADHESIVE PROTECTIVE FOR WELDING

ITEM: SPRAYMIG H20

[SAFETY DATA SHEETS ON-LINE](#)

Protects torches and welding pieces, prevents adhesion to metallic parts at high temperatures. Ecological silicone-free and dichloromethane, non-flammable.

Tech. Code		Package	Quantity ml	
J8425400		Spray can	400	12