

## AUTOMATIC SHRINKING MACHINE

### ITEM: ISG3410 WK

The ISG3410 WK shrink-fit machine performs the shrink function, cooling and drying of the chuck in complete automatism, without any operator intervention.

The graphic and intuitive display simplifies every operation.  
The machine is supplied with 4 Interchangeable rings  $\varnothing$  3 - 32mm,  
1 liter of coolant, protective gloves and user manual.

The tool holders must be ordered separately C4610xx

Tech. Code		C46051
Shrinking range	$\varnothing$ HM	3 - 32
Shrinking range	$\varnothing$ HSS	6 - 32
Tool length	max mm	400 with HSK63
Cooling time		20"
Power	kW	11
Power supply		400V - 16A - 50Hz
Compressed air	bar	4
Dimension	mm	800 x 560 x 1720

## MANUAL SHRINKING MACHINES

### ITEM: ISG1000

The ISG1000 shrink-fit machine is the most advantageous solution either economically or from a performance point of view for a first approach to the use of shrink-fit chuck. It is simple to use, its small size makes it the most versatile shrink-fit machine on the market today.

The machine is supplied with 1 Interchangeable ring 6 - 16 mm, protective gloves and user manual.

The holders must be ordered separately C4625xx

Tech. Code		C46201
Shrinking range	$\varnothing$ HM	3 - 16
Shrinking range	$\varnothing$ HSS	12 - 16
Tool length	max mm	290 with HSK63
Cooling		NO
Power	kW	6,5
Power supply		400V - 16A - 50Hz
Dimension	mm	390 x 310 x 640

## AIR COOLING UNIT FOR ISG1000

### ITEM: ISGK L 1000

The ISGK L 1000 air cooling unit was designed specifically to be combined with the ISG1000 shrink-fit unit.

It can be assembled together with the shrink unit with a simple manual movement of the tool (together with its holder) in about 20 seconds cooling down is obtained.

For a more effective operation of the equipment we recommend the use of the units C4628xx cooling adapters.

Tech. Code		C46211
Power supply		230V - 16A
Dimension	mm	390 x 190 x 110