

REVERSIBLE AIR RATCHET WRENCHES

ITEM: 107XPA

Air ratchet wrench with a 3/8" coupling and proven reliability. This is one of the world's best-selling wrenches. The 1077XPA with an advanced head design offers a longer service life. Maximum torque of 73 Nm and a 360° adjustable exhaust directs air away from the operator, speed regulator lever.

Power supply: Lubricated compressed air - Recommended pressure 6.3 Bar

Tech. Code	L007038	
Square coupling	3/8"	
Working torque range	Nm	14 - 61
Max torque	Nm	73
Rpm	max.	160
Air inlet connector - consumption	1/4" NPT - 528 l/min	
Air inlet hose	Ø	10
Noise level	dBA	94.4
Vibration*	m/s ² /K	<2.5
Weight	Kg	1.24

* ISO28927 - 3-axis measurement: vibration level/measurement uncertainty.

276 mm

REVERSIBLE AIR RATCHET WRENCHES

ITEM: L0015

Steel/composite housing, suitable for use in awkward positions.

Power supply: Lubricated compressed air - Recommended pressure 6.3 Bar

Tech. Code	L001512	
Square coupling	1/2"	
Max screw Ø	M12	
Max torque	Nm	95
Rpm	max.	160
Noise level	dBA	91.6
Air inlet connector - consumption	1/4" NPT - 520 l/min	
Vibration level (ISO 28927-2)	m/s ²	3.28
Weight	Kg	1.26

293 mm

ON-LINE
MANUAL

REVERSIBLE AIR RATCHET WRENCHES

ITEM: 1077XPA

Air ratchet wrench with 1/2" coupling and proven reliability, the 107XPA with an advanced head design is one of the world's best-selling wrenches. Maximum torque of 73 Nm and a 360° adjustable exhaust directs air away from the operator, speed regulator lever.

Power supply: Lubricated compressed air - Recommended pressure 6.3 Bar

Tech. Code	L007212	
Square coupling	1/2"	
Working torque range	Nm	14 - 61
Max torque	Nm	73
Rpm	max.	160
Air inlet connector - consumption	1/4" NPT - 528 l/min	
Air inlet hose	Ø	10
Noise level	dBA	94.4
Vibration*	m/s ² /K	<2.5
Weight	Kg	1.25

* ISO28927 - 3-axis measurement: vibration level/measurement uncertainty.

276 mm

RIGHT ANGLE IMPACT WRENCHES

ITEM: 2025MAX

The MAX series right angle impact wrenches guarantee top-level performance, power and control are equipped with an Ingersoll Rand **Jumbo hammer** impact mechanism. Ideal for professional assembly and maintenance technicians when working in areas that are difficult to access.

Power supply: Lubricated compressed air - Recommended pressure 6.3 Bar

Tech. Code	L007512	
Coupling	1/2"	
Working torque	Nm	217
Max torque	Nm	244
No-load speed	Rpm	7100
Blows per minute	2100	
Air inlet connector - consumption	1/4" NPT - 538 l/min	
Air inlet hose	Ø	10
Noise level	dBA	96.6
Weight	Kg	1.54

* ISO28927 - 3-axis measurement: vibration level/measurement uncertainty.

332 mm