

SPRING BALANCERS FLEX LIGHT SERIES

ITEM: FLEX TYPE B

Sheet steel housing. Spring with adjustable load. Adjustable cable run. Safety device against spring break. Suitable for the balanced suspension of tools and frames.

Tech. Code	L2100005015	L2100010020	L2100020035	L2100030060	L2100050085	L2100080110
Load capacity kg	0.5-1.5	1-2	2-3.5	3-6	5-8.5	8-11
Cable length m	2.30					
Cable	Braided nylon			Coated steel		
Weight kg	0.60	0.65	1.65	1.70	1.75	

*Steel cables may be supplied upon request.

SPRING BALANCERS MATIC WITH COMPRESSED AIR HOSE

ITEM: MATIC

Composite material housing. Spring with adjustable load. Adjustable hose run. Specifically designed for pneumatic tools, the feeding hose is also the tool supporting cable.

Tech. Code	L2105005015	L2105015030	L2105030050
Load capacity kg	0.5-1.5	1.5-3	3-5
Pipe length m	1.60		
Fitting	1/4" M		
Weight kg	1.6	1.7	1.8

SPRING BALANCERS - LIGHT SERIE RUN 1600

ITEM: 9311 - 9312 - 9313

Structural characteristics:

- Suitable for the assembly lines
- Indicated for the use of electrical and pneumatic tools

Advantages:

- Reduces the operator's labour
- Reduces the working time
- Improves the quality of work
- Limits the damage to tools and risks to people

Tech. Code	L2200002005	L2200004010	L2200010020	L2200020030
Load capacity Kg	0.2 ÷ 0.5	0.4 ÷ 1	1 ÷ 2	2 ÷ 3
Weight Kg	0.55	0.6	0.7	
Run mm	1600			
Cable	Inox			
Cap	Aluminum			

