

AIR COMPRESSORS CO-AXIAL SINGLE-STAGE LUBRICATED

ITEM: SILVERSTONE L25P

The pumping unit mounted directly on the rotating shaft of the electric motor makes these compressors lightweight and exceptionally compact. The lubrication system for the moving parts prevents overheating and increases service life.

Tech. Code		L629010
Tank	L	10
Power	Hp/kW	2.5/1.9
Rpm	max	2850
Inlet flow rate	l/min	270
Power supply	V/Hz	230/50
Max. pressure	Bar	10
Dimensions	mm	420 x 330 x 635
Weight	Kg	24

ITEM: POLE POSITION L20

Compact and lightweight, thanks to the pumping unit mounted directly on the rotating shaft of the electric motor, the lubrication system of the moving mechanical parts prevents overheating and increases durability.

Tech. Code		L630024
Tank	L	24
Power	HP/Kw	2 - 1.5
Rpm	max	2850
Air inlet	l/min	220
Power	Voltage	230
Max pressure	Bar	8
Dimension	mm	570 x 255 x 590
Weight	kg	25

ITEM: MONTECARLO L20

Compact and lightweight, thanks to the pumping unit mounted directly on the rotating shaft of the electric motor, the lubrication system of the moving mechanical parts prevents overheating and increases durability.

Tech. Code		L630550
Tank	L	50
Power	HP/Kw	2 - 1.5
Rpm	max	2850
Air inlet	l/min	220
Power	Voltage	230
Max pressure	Bar	8
Dimension	mm	770 x 310 x 645
Weight	kg	33