



ELECTRIC REVERSIBLE DRILLS

ITEM: GBM 10 RE PROFESSIONAL

Supply voltage 230 Volt, powerful and compact, electronic control for a precise initial drilling phase. Auto-locking metal chuck for high precision and long service life, with anti-loosening safety screw during left-hand rotation, handle with Softgrip coating for a secure and comfortable grip, practical belt clip attachment, 43 mm collar Ø for use on a column support.

Tech. Code		N4100600/1
Power	W	600
No-load speed	Rpm	0-2600
Threaded shaft coupling		3/8"
Chuck	mm	10
Ø Max. drilling - Steel	mm	10
Ø Max. drilling - Aluminium	mm	10
Ø Max. drilling - Wood	mm	25
Weight	Kg	1,7

Included:
Keyless chuck

Dimensions: 249 x 194 h mm



ITEM: GBM 13-2 RE PROFESSIONAL

Supply voltage 230 Volt, powerful and accurate, fully equipped with ball and roller bearings for long service life and precise work, pre-set number of revolutions with setting wheel. Auto-locking metal chuck for high precision and long service life, with anti-loosening safety screw during left-hand rotation, 43 mm collar Ø for use on a column support.

Tech. Code		N4103750/1
Power	W	750
No-load speed	Rpm	0-1000/3200
Threaded shaft coupling		1/2 UNF
Chuck	mm	1,5-13
Ø Max. drilling - Steel	mm	13/8
Ø Max. drilling - Aluminium	mm	20/12
Ø Max. drilling - Wood	mm	32/20
Weight	Kg	2,4

Included:
Auxiliary handle
Depth stop 210 mm
Keyless chuck high precision

Dimensions: 332 x 208 h mm



ELECTRIC REVERSIBLE DRILLS

ITEM: BOP 6

Compact drills with optimal Rpm for small diameter holes. FEIN® high-performance motor with variable speed, right and left rotation. Equipped with SUPRA SKE steel quick-release chuck and Senitiv handle FEIN®, 5 meter cable.

Tech. Code		N410206
Power supply	V	230 - 50 Hz
Power	W	500
No-load speed	Rpm	0 - 4000
Threaded shaft coupling		1/2 20 UNF
Chuck	mm	0,5 - 10
Ø Max. drilling - Steel	mm	6
Ø Max. drilling - Aluminium	mm	10
Ø Max. drilling - Wood	mm	20
Weight	Kg	1,7

Included:
Chuck
Handle

ITEM: BOP 10

Compact variable speed drills with high Rpm stability, suitable for holes in steel up to 10 mm. FEIN® high-performance motor with right and left rotation. Equipped with SUPRA SKE steel quick-release chuck and FEIN® Sensitiv handle. 5 meter cable.

Tech. Code		N410410
Power supply	V	230 - 50 Hz
Power	W	500
No-load speed	Rpm	0 - 1500
Threaded shaft coupling		1/2 20 UNF
Chuck	mm	1,5 - 13
Ø Max. drilling - Steel	mm	10
Ø Max. drilling - Aluminium	mm	15
Ø Max. drilling - Wood	mm	30
Weight	Kg	1,8

Included:
Chuck
Handle