HALF ROUND LONG BENT NOSE PLIERS

ITEM: 38 25 200

STANDARD DIN/ISO 5745

Pliers for fine mechanics with half-round long bent nose and knurled tips. Chrome-vanadium steel forged and oil-hardened, handles coated in multil-component material.

	Tech. Code	Length mm	Jaws mm
I	F0285200	200	73

ITEM: 25 25 160

STANDARD DIN/ISO 5745

Chrome-vanadium chrome-plated forged and oil-hardened pliers, Induction tempered cutting edges with hardness approx. 61 HRC.

Half-round bent at 40 ° with pointed ends and cutting edge for metal wire with low and medium strength knurled resistant end tips. Handles covered in two-component material.

	Tech. Code	Length mm	Jaws mm	Steel wire ø max mm
I	F0218160	160	50	1.6

ITEM: 26 22 200

STANDARD DIN/ISO 5745

Chrome-plated pliers with cutter, half-round long bent nose pliers with knurled tips and cutting edges for metallic wire of medium and high resistance. Cutting edges further tempered with Induction hardness approx. 61 HRC.

Forged and oil-hardened chrome-vanadium steel Insulated handles coated in synthetic resin material.

	Tech. Code	Length mm	Jaws mm	High resistant wire Ø max mm
I	F0283200	200	73	2,2

ITEM: 26 25 200

STANDARD DIN/ISO 5745

Chrome-vanadium chrome-plated forged and oil-hardened pliers, Induction tempered cutting edges with hardness approx. 61 HRC.

Half-round bent at 40 ° with pointed ends and cutting edge for metal wire with low and medium strength knurled resistant end tips. Handles covered in two-component material.

	Tech. Code	Length	Jaws	Steel wire
recii. code	10011. 0000	mm	mm	Ø max mm
I	F0219200	200	73	2.2

WODEX ♦ HALF ROUND BENT NOSE PLIERS VDE INSULATED 1000 V

ITEM: WX3230

STANDARD DIN/ISO 5745



Pliers with cutting nipper with half round long bent nose PREMIUM QUALITY made of chromiummolybdenum steel with satin finish, cutting of high resistance extra precise induction hardened nose with knurled grip surface. Insulated handles up to 1000 V DIN EN 60900 / VDE 0682-201. Hardness: handles 43-48 HRC, cutting nipper 58-60 HRC.

ERGOFORM grip handles hypoallergenic, anti-slip, soft and comfortable in SANTOPRENE® that are compliant with

RoHS e REACH directives.

	Tech. Code	Length mm	Jaws mm	Hardness cutting HRC
I	F0278200	200	68	58-60