

CABLE SHEARS FOR VDE INSULATED CABLES 1000 VOLTS

ITEM: 95 16 165

Shears for cutting copper and aluminum cables, which can not be used for steel wire or cold drawn copper cables. Cold, clean cut without crushing with contrast stop to avoid accidental crushing of the fingers. Special steel for hardened, forged and oil-hardened tools, VDE tested, compliant with EC 60900 DIN EN 60900 standard.



Tech. Code	Cables Ø max mm	Length mm
F2201165	15	165

CABLE SHEARS FOR INSULATED CABLES 1000 VOLTS

ITEM: 95 16 200

Shears for cutting copper and aluminum cables which can not be used for steel wire or cold drawn copper cables. Cold, clean cut without crushing, subdividing the cutting operation in the first cut (for insulating sheath, in front area of the cutting edge) and finishing cut (for the conductor, in the rear area of the cutting edge) It is possible to cut cables up to 20 Ø with one single hand. With contrast stop to avoid accidental finger crushing.

Special steel for tempered, forged, oil-hardened tools, handle coated in bi-component material. VDE tested, compliant with EC 60900 DIN EN 60900 standard.



Tech. Code	Cables Ø max mm	Length mm
F2202200	20	200

BOLT CUTTERS COMBICUT® 433

ITEM: COMBICUT® 433

Compact and handy bolt cutters with head in special high quality forged tempered steel, top of the range distinguished by a yellow dot, to cut medium and strength steel.

- Cutting force up to 48 HRc
- No need for blade adjustments
- Reduction of separation effort due to optimal geometry
- Small dimension for insertion of tool boxes

Tech. Code	Length mm	19 HRc Ø max mm	40 HRc Ø max mm	48 HRc Ø max mm
F23000390	390	7	5	4

SPARE CUTTER HEADS FOR BOLT CUTTERS COMBICUT® 433

ITEM: COMBICUT® 433/1

Spare cutter heads for bolt cutters VBW Combicut® 433 complete with pins and elastic rings.

Tech. Code	For bolt cutters mm	19 HRc Ø max mm	40 HRc Ø max mm	48 HRc Ø max mm
F23010390	390	7	5	4

END-CUTTING BOLT CUTTERS COMBICUT® 433V

ITEM: COMBICUT® 433V

End-cutting bolt cutters, compact and handy with head in special forged steel, high quality tempered steel, top of the range, distinguished by a yellow dot, to cut steel of medium and high resistance.

- Cutting force up to 48 HRc
- No need for blade adjustment
- Reduction of separation effort thanks to optimal geometry
- Small dimensions for insertion of tool boxes

Tech. Code	Length mm	19 HRc Ø max mm	40 HRc Ø max mm	48 HRc Ø max mm
F23020370	370	7	5	4

SPARE CUTTER HEADS COMBICUT® 433V

ITEM: COMBICUT® 433V/1

Spare cutter heads for bolt cutters VBW Combicut® 433V complete with pins and elastic rings

Tech. Code	For bolt cutters mm	19 HRc Ø max mm	40 HRc Ø max mm	48 HRc Ø max mm
F23030370	370	7	5	4