## **BATTERY RIVETERS**

#### ITEM: M12 BPRT-201X

M12 BPRT-201X cordless riveting machine applies up to 325 4.8 mm stainless steel rivets with a single charge of a 2.0 Ah battery. Suitable for the application of rivets in aluminum, stainless steel and copper, with a diameter of Ø 2.4 mm up to a solid piece of Ø 4.8 mm. Stroke length of 20 mm. Clamps accessible without the use of tools. Possibility of storing the nozzles in the practical compartment placed on the tool.

Works with all Milwaukee® M12 ™ batteries.

Tech. Code		F834012
Battery capacity	Ah	2
Blade stroke	mm	20,32
Ø jaw max.	mm	2,4 - 4,8
Traction force	N	9000
Weight with battery	Kg	2,1
Battery charging time	min	40
Battery type		Li-ion
Voltage	V	12

Supplied with:

- 1 battery 12V da 2,0 Ah
- 1 battery charger
- carrying case

ON-LINE MANUAL

## PNEUMATIC RIVETERS FOR BLIND RIVETS

#### ITEM: RAC 83/95

Cast aluminum body, steel operating parts. Supplied complete with four nozzles.

Te	ech. Code	Rivets ø	Weight
F	8350RP/1	mm 2,4 + 4,8 *	1500

<sup>\* 4,8</sup> ø only made from aluminium

## ITEM: RAC 83 AX

Model with rivet retention and sliced nail recovery. Cast aluminum body, steel operating parts, supplied complete with four nozzles.

1	Tech. Code	Rivets ø	Weight
1		mm	g
I	F8360RP/2	2,4 + 4,8 *	1500

<sup>\* 4,8</sup> ø only made from aluminium

# **OLEO-PNEUMATIC RIVETERS FOR BLIND RIVETS**

### ITEM: RAC 181

Model with rivet retention and sliced nail recovery. Cast aluminium body, steel operating parts, supplied complete with six nozzles.

Tech. Code	Rivets ø mm	Weight
F8380ROP/1	2,4 - 6 *	1600

<sup>\* 6</sup> ø only made from aluminium