

OLEO-PNEUMATIC RIVETERS FOR THREADED INSERTS

ITEM: EXTRA KJ60

Plastic shock-proof body, steel operating parts.

Plastic case containing riveter KJ60 with nozzles and heads M3 ÷ M8.

Tech. Code		Inserts capacity	Weight g
F8450ROP/2		M3 ÷ M8	2200

The weight refers to each single machine.

Spare tie rod for KJ60

Tech. Code		Dimension
F8455M3		M3
F8455M4		M4
F8455M5		M5
F8455M6		M6
F8455M8		M8

ITEM: KJ45 S

Body in shock-resistant plastic and steel operating parts.

Plastic case containing riveter KJ45 with rods and heads M4 + M12.

Tech. Code		Inserts capacity	Weight g
F8460ROP/3		M4 ÷ M12	2860

The weight refers to each single machine

Spare tie rod for KJ45 S

Tech. Code		Dimension
F8465M4		M4
F8465M5		M5
F8465M6		M6
F8465M8		M8
F8465M10		M10
F8465M12		M12

THREADED INSERTS WITH ROUND HEAD IN GALVANIZED STEEL

ITEM: F8480

Threaded inserts short version with round head in C43 steel
(EN 1.0303) / C10C (EN1.0214)

Surface treatment:

White zinc plating with a minimum thickness of 7Micron
(Fe / Zn 7 IV).

M3 size without knurling on the stem.

Tech. Code		M	L mm	Hole mm	e mm	D mm	B mm	S mm	r mm	Pieces per pack
F848003		3	9	5	0,3 ÷ 1,8	4,9	7	0,8	6,0	200
F848004		4	11	6		5,9	9	1,0	7,5	
F848005		5	13	7	0,5 ÷ 3,0	6,9	10	1,2	9,5	
F848006		6	14,5	9		8,9	12	1,5	10,0	
F848008		8	17,5	11	0,8 ÷ 3,5	10,9	15		11,4	
F848010		10	21	13	1,0 ÷ 3,5	12,9	17	1,7	14,5	

The displayed price refers to the 200 piece pack.