

WHEEL BRUSHES

ITEM: G4905

High resistant crimped wire. For deburring, etching and polishing.

K = multihole reduction kit 25-20-16

Tech. Code		D mm	E mm	S mm	C mm	F mm	Wire	Max speed RPM
G4905100		100	20	19	28	16	Steel Ø 0.35	6.000
G4905150		150	27	36	38	K		
G4905150/1			20	32				
G4905200		200	29	44		4.500		
G4905200/0			23					
G4905250		250	30	65	58	38+K		3.600
G4905150/2		150	27	32	38	K	Steel Ø 0.50	6.000
G4905200/1		200	29	47				4.500
G4905100/0		100	12	25	-	12	Brass-plated steel Ø 0.30	6.000
G4905150INOX		150	27	36	38	K	Stainless steel Ø 0.30	
G4905200INOX		200	29	44				



WHEEL BRUSHES TWIST KNOTTED WIRE

ITEM: G4908

Aggressive brush, suitable for removing burning and rust. Cleaning of fillet weld and elimination of adhesive residues.

Tech. Code		D mm	E mm	S mm	F mm	Wire	Max speed RPM
G4908115		115	12	22	22,2	Steel Ø 0.50	12.500
G4908125		125		28			11.000
G4908115IN		115		22		Stainless steel Ø 0.35	12.500
G4908125IN		125		28			11.000



DISC BRUSHES WITH HOLE

ITEM: G4909

Exceptional removal of soft materials such as underseal or antidrumming compound. Particular filament geometry provides porous surfaces similar to sanded ones. Cooling effect. It does not obstruct. Used for angle or straight angles.

Tech. Code		D mm	E mm	S mm	F	Wire	Max speed RPM
G490910020		100	20	18	M14 x 2	Steel Ø 0.60	6.000

BEVEL BRUSHES

ITEM: G4911

Cone-shaped brushes suitable for uneven surfaces and surfaces with sharp edges. Suitable for removing scale, rust and residues from various materials. The crimped steel wires are extremely high strength and provide a long service life.

Tech. Code		D mm	S mm	F	Wire	Max speed RPM
G4911090		90	20	M14	Steel Ø 0.35	14.000
G4911120		120	22			12.500
G4911090IN		90	20		Stainless steel Ø 0.30	14.000
G4911120IN		120	22			12.500



THREADED BEVEL TWIST KNOTTED BRUSHES

ITEM: G4912

Aggressive brush. Excellent for heavy duty brushing, deburring e rust removal. The conical shape facilitates reaching difficult areas such as inner corners, grooves and gorges.

Tech. Code		D mm	S mm	F	Wire	Max speed RPM
G4912115		115	26	M14 x 2	Steel Ø 0.50	15.000
G4912115IN					Stainless steel Ø 0.35	