

MEASUREMENT INSTRUMENTATION ICONS

Centesimal measurement	Millesimal measurement	Bi-Millesimal measurement	Five-Millesimal measurement
DIN Standard	LCD display	Deci-Millesimal measurement	Decimal measurement
Hardened stainless steel	mm/inch conversion	LCD display with big numbers	Control report with declaration of conformity
Bluetooth	Spindle Ø 6.5mm	Spindle Ø 8mm	Data output
1.5V Lithium battery - CR	3V Lithium battery - CR 2032	9V Lithium battery	MD contact surfaces
Standby mode (10 min.)	Operating temperature	Storage temperature	IP54 standard
Rigid housing (metal, wood or plastic)	Soft housing	EN 50081-1, EN 50082-1	IP65 standard
Rotating dial	Spherical measuring contact, Ø 3mm, mounted	Accurate design	IP66 standard
ABS - Absolute zero	Round depth rod mm 1.5	Standard depth rod (flat)	IP67 standard

ALPAA DIGITAL CALIPERS IP67 WITH PRESET

MEGAtry EVO



ITEM: AA014

0,01 mm Resolution - Digital caliper with Swiss technology, unrivaled protection against penetration of particles and liquids. Vernier with locking screw system, automatic on/off button, auto power off after 20 minutes of inactivity, incremental measuring and zero-setting at any position, data output. Memorized position in pause mode with maximum speed displacement of 2.5 m/sec. Structure mechanics tempered, rectified stainless steel, superior comfort thanks to its ergonomic design and sturdy structure, 3,5 mm. Preset function included.

Tech. Code	Measuring range mm	A mm	B mm	C mm	D mm	E mm	Rod
D0010150NDP	0 ÷ 150	235	40	11	16	16 x 3,5	■
D0010150P							●
D0010150NDT							●
D0010150T							●
D0010200	0 ÷ 200	290	50	14	19	16 x 4	■
D0010300	0 ÷ 300	388	64				-

Model D0010...ND without data output.

Tech. Code	Model
D99113V	Battery 3V DL2032 - CR2032
D0002USB	Connection cable Proximity-USB
D0002RS232	Proximity -cable RS232

ON-LINE MANUAL

