

SCREW CLAMPS REINFORCED SERIES SGM

ITEM: SGM

High quality galvanized steel, clamping force up to 12,000 N at a tightening torque of 40 Nm, long service life due to the tilting pressure plate with hardened steel insert.

Tech. Code		Opening mm	Depth mm	Rod diameter mm	Weight Kg
F66170250		250	140	34 x 13	2.5
F66170300		300			3.0
F66170400		400			3.1
F66170500		500			3.4
F66170600		600			3.8
F66170800		800			4.4
F66171000		1000			4.9
F66171250		1250			5.8
F66171500		1500			6.6

HEAVY DUTY SCREW CLAMPS STBM

ITEM: STBM

High performance screw clamps for heavy metal fabrication.

High quality galvanized steel, clamping force up to 22,000 N at a tightening torque of 70 Nm, long service life due to the tilting pressure plate with hardened steel insert.

Screw with 19 mm hexagonal nut.

Tech. Code		Opening mm	Depth mm	Rod diameter mm	Weight Kg
F66190300		300	175	40 x 20	5.6
F66190400		400			6.1
F66190500		500			6.6
F66190600		600			7.2
F66190800		800			8.3
F66191000		1000			9.3
F66191250		1250			10.7
F66191500		1500			12.2

SCREW CLAMPS WITH DEEP THROAT SGTM

ITEM: SGTM

High quality galvanized steel, clamping force up to 8,500 N at a tightening torque of 40 Nm, long service life due to the tilting pressure plate with hardened steel insert.

Throat depth up to 200 mm

Tech. Code		Opening mm	Depth mm	Rod diameter mm	Weight Kg
F6621300		300	200	30 x 15	3.4
F6621600		600			4.3

LEVER CLAMPS GH

ITEM: GH

High quality galvanized steel, movable jaw with tilting pressure plate and quick clamping lever at the end of the stroke, the lever is vertical.

Clamping force up to 8,500 N

Tech. Code		Opening mm	Depth mm	Rod diameter mm	Weight Kg
F6600120		120	60	15 x 6	0.49
F6600160		160	80	17.5 x 6.8	0.64
F6600200		200	100	22 x 8.5	1.11
F6600250		250	120	24.5 x 9.5	1.44
F6600300		300	140	28 x 11	2.22
F6600400		400	120		2.41
F6600500		500			2.61
F6600600		600			2.78
F6600800		800			3.14
F66001000		1000			3.59